

DIRACNICIONIC

CIICDFNICIONI

<u>ROTAX" ENGINE</u>	900 ACE
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	3
Displacement	899.0 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Regular unleaded
Minimum octane	95
Fuel tenk	40 litoro

IIOIIUL EIIOIILE	5557.52
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	3
Displacement	899.0 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Regular unleaded
Minimum octane	95
Fuel tank	40 liters

r ovuliiiniin	
Drive clutch type	eDrive II
Driven clutch type	QRS SS
Small sprocket number of teeth	1st gear = 3.23:1 ratio
Large sprocket number of teeth	2nd gear = 1.98:1 ratio
Drive sprocket	7
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

<b>COLOUR</b>	Black/Anniversary Copper
---------------	--------------------------

DIIVIEIVƏIDIVƏ	
Vehicle overall length	3370 mm
Vehicle overall width	1180 mm
Vehicle overall height	1445 mm
Ski stance	996 +/- 21 mm
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	44 mm

Front suspension	A-LFS+ with bended lower A-Arms
Front shock	HPG 36
Rear suspension	PPS-5900-A
Center shock	HPG 36
Rear shock	HPG 36

## **FEATURES**

DNINFRTRAIN

2018

Frame	L-XU
Skis	Blade XC
Seating	Modular, 1+1 (heated rider seat)
Handlebar	Steel with hooks, mountain strap
Riser block height	Adjustable 130-205 mm
Starter	Electric
Reverse	Mechanical (2F-N-R)

Standard
Standard
Multifunction
Accessory
High (510 mm), one piece
Standard

