

# XTRIM

## 2018



### ROTAX® ENGINE

#### 600 ACE

Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Regular unleaded
Minimum octane	95
Fuel tank	38 liters
Oil tank capacity (2-stroke)	-

### POWERTRAIN

Drive clutch type	eDrive
Driven clutch type	QRS SS
Small sprocket number of teeth	21
Large sprocket number of teeth	51
Drive sprocket	8
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

### FEATURES

Frame	REX <sup>2</sup>
Skis	Blade DS
Seating	1-up
Handlebar	Straight steel with hooks
Riser block height	160 mm
Starter	Electric
Reverse	Mechanical

### COLOUR

 White/Red/Black

### DIMENSIONS

Vehicle overall length	3170 mm
Vehicle overall width	1180 mm
Vehicle overall height	1320 mm
Ski stance	996 +/- 21 mm
Track nominal width	406 mm
Track nominal length	3705 mm
Track profile height	39 mm DSG

### SUSPENSION

Front suspension	A-LFS+
Front shock	HPG 36
Rear suspension	PPS <sup>2</sup> -3700
Center shock	HPG 36
Rear shock	HPG 36