

2021

MXZ X-RS[®] IRON DOG

AVAILABLE UNTIL APRIL 16, 2020

PACKAGE HIGHLIGHTS

- Rotax[®] 600R E-TEC[®] engine
- REV[®] Gen4 platform with narrow-design bodywork
- Reinforced frame
- pDrive[™] clutch
- RAS[™] X front suspension
- rMotion[™] X rear suspension
- KYB Pro 40 R front shocks and KYB Pro 40 rear shocks aluminum piggyback with Easy-Adjust compression adjuster (22 clicks), race ready calibration
- Brembo racing brake with braided stainless-steel brake line
- Low windshield with side deflectors
- Handguards
- RER[™] electronic reverse
- Performance trail seat
- Backlit multifunction steering controls
- RS running boards
- Rail stiffeners
- Rack steering system
- 381 x 3,277 x 40.6 mm (15 x 129 x 1.6 in.) Cobra



Image is indicative

ROTAX[®] ENGINE

600R E-TEC[®]

Engine details	Liquid-cooled, eRAVE [™]
Cylinders	2
Displacement	599.4 cc
Bore	72.3 mm
Stroke	73 mm
Maximum engine speed	8,100 RPM
Carburation	E-TEC direct injection
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	36 L
Oil tank capacity	3.4 L

POWERTRAIN

Drive clutch type	pDrive [™] with clickers
Driven clutch type	QRS
Engagement	3,400 RPM
Small sprocket number of teeth	25
Large sprocket number of teeth	51
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm
Brake system	Brembo racing brake with stainless-steel braided brake line

COLOR

Black

DIMENSIONS

Vehicle overall length	2,925 mm
Vehicle overall width	1,217 mm
Vehicle overall height	1,222 mm
Ski stance	1,069 - 1,092 - 1,115 mm
Track nominal width	381 mm
Track nominal length	3,277 mm
Track profile height	41 mm Cobra

SUSPENSION

Front suspension	RAS [™] X
Front shock	KYB [®] Pro 40 R Easy-Adjust
Front suspension max. travel	265 mm
Rear suspension	rMotion [™] X
Center shock	KYB [®] Pro 40 Easy-Adjust
Rear shock	KYB [®] Pro 40 Easy-Adjust
Rear suspension max. travel	292 mm

FEATURES

Frame	REV [®] Gen4	Riser block height	120 mm	Mirrors	Optional
Bodywork	Narrow design	Starter	Manual	Windshield	Low
Skis	Pilot [™] X	Reverse	RER [™]	Runner	Round 7/16
Seating	Trail performance	Heated throttle lever/ grips	Standard	Carbide configuration	102 mm at 90°
Handlebar	U-shaped aluminum with J-hooks	Gauge	VIP-MID	Hitch	Optional

ski-doo

