

2021 SKANDIC WT **NEW**

// WHAT'S NEW

- 20 x 154 x 1.5 in. Cobra WT
- Pilot 7.4 skis
- 4.5-in. digital display
- and much more!

// PACKAGE HIGHLIGHTS

- Rotax® 900 ACE™ engine with 650W magneto available
- LTS telescopic front suspension
- pDrive™ clutch
- 20-in. wide Multi-LinQ plate with 56.7 kg cargo capacity
- SC™-5U articulating rear suspension with locking mechanism on one side (no tool required)
- Air radiator with fan
- Easy Shift transmission (H-L-N) with RER™ electro-mechanical reverse
- Removable passenger seat and with grips
- 27.5-in. Ultra-high windshield with side deflectors
- Pivoting mirrors
- Deep snow running boards with large openings
- Low handlebar strap
- Hitch



SKANDIC® WT 900 ACE™ SHOWN

// EXTRA HIGHLIGHTS

ACE™ ENGINES

- Rotax® engines with 650W magneto
- Reversible throttle lever (thumb or finger activated)
- iTC™ Engine mapping modes (Standard, Sport, or ECO)
- High efficiency air radiator with fan

ROTAX® ENGINE

900 ACE™

	Liquid-cooled, four-stroke D.O.H.C., dry sump
Engine details	
Cylinders	3
Displacement	899 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7,250 RPM
Carburation	EFI
Recommended fuel type	Unleaded 95
Fuel tank	42 L
Oil tank capacity	3.3 L

POWERTRAIN

Drive clutch type	pDrive™ with slider shoes
Driven clutch type	QRS
Engagement	2,200 RPM
Small sprocket number of teeth	Lo = 4.24:1 ratio
Large sprocket number of teeth	Hi = 2.36:1 ratio
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm
Drive sprocket pitch	73 mm
Brake system	Brembo brake with stainless-steel braided brake line

SUSPENSION

Front suspension	LTS
Front shock	Motion Control
Front suspension travel	150 mm
Rear suspension	SC™-5U
Center shock	Motion Control
Rear Shock	HPG™
Rear suspension travel	239 mm

COLOR

Lava Red / Black

DIMENSIONS

Vehicle overall length	3,222 mm
Vehicle overall width	1,089 mm
Vehicle overall height	1,513 mm
Ski stance	889 mm
Track (Length x Width x Profile)	Cobra WT: 154 x 20 x 1.5 in. (3,923 x 500 x 38 mm)

FEATURES

Frame	REV® Gen4
Bodywork	Wide design
Skis	Pilot™ 7.4
Seating	2-up modular with underseat storage
Handlebar	U-shaped aluminum with J-hooks / Low grab handle
Riser block height	145 mm
Starter	Electric
Reverse	Mechanical
Heated throttle lever / grips	Standard (driver only)
Gauge type	4.5-in. digital display
Windshield	673 mm with mirrors
Runner	Square 3/8
Carbide configuration	102 mm at 90°
Bumpers (Front/Rear)	Std / Heavy Duty with hitch

ski-doo

A BRP BRAND





SKANDIC® 900 ACE™ SHOWN

// FEATURE HIGHLIGHTS



REV® Gen4 platform

Lightweight, strong and durable built to accommodate 20-in. wide tracks to maximize flotation and traction, while providing the precise handling and benefits of the open cockpit design. Maximum comfort and capability on- and off-trail.



SC™-5U articulating rear suspension

Features settings that maximize deep snow traction in reverse or lock out for towing.



Easy Shift transmission (H-L-N) with push-button reverse

Easily shifts with multiple gear ratios. Built for heavy duty reliability with high load resistance and optimal lubrication. Handlebar push-button engages reverse - electronic RER™ with E-TEC engine choice, electro-mechanical with ACE™ engines.



Utility 2-up seat with passenger handholds

2-up seat with integrated back support, including handholds.