

# XTERRAIN



## ROTAX® ENGINE

	600 EFI	600R E-TEC
<b>Engine details</b>	Liquid-cooled, two-stroke	Liquid-cooled, two-stroke, 3-D R.A.V.E.™
<b>Cylinders</b>	2	2
<b>Displacement</b>	599.4 cc	599.4 cc
<b>Bore</b>	72.3 mm	72,3 mm
<b>Stroke</b>	73 mm	73 mm
<b>Maximum engine speed</b>	7500 RPM	8100 RPM
<b>Carburation</b>	EFI	Electronic Direct Injection
<b>Recommended fuel type</b>	Unleaded	Unleaded
<b>Minimum octane</b>	95	95
<b>Fuel tank</b>		37 liters
<b>Oil tank capacity (2-stroke)</b>		3,4 liters

## COLOUR

Race Orange/Black

## DIMENSIONS

<b>Vehicle overall length*</b>	3160 mm (3700) 3270 mm (3900)
<b>Vehicle overall width</b>	1200 mm
<b>Vehicle overall height</b>	1250 mm
<b>Ski stance</b>	996 mm
<b>Track nominal width</b>	406 mm
<b>Track nominal length</b>	3705 mm 3923 mm
<b>Track profile height</b>	51 mm PowderMax

## POWERTRAIN

<b>Drive clutch type</b>	pDrive with clickers (600R E-TEC) pDrive (600 EFI)
<b>Driven clutch type</b>	QRS
<b>Brake system</b>	Hydraulic brake with braided steel brake line, plastic master cylinder

## SUSPENSION

<b>Front suspension</b>	LFS
<b>Front shock</b>	HPG 36
<b>Rear suspension</b>	PPS <sup>2</sup> -DS+ -3700 PPS <sup>2</sup> -DS+ -3900
<b>Center shock</b>	HPG 36
<b>Rear shock</b>	HPG 36

## FEATURES

<b>Frame</b>	Radien	<b>Heated throttle lever</b>	Standard
<b>Skis</b>	Blade DS+	<b>Heated grips</b>	Standard
<b>Seating</b>	Sport, 1-up	<b>Gauge</b>	4.5-in. digital display
<b>Handlebar</b>	U-type aluminium with hooks, low grab handle	<b>Windshield</b>	Low
<b>Riser block height</b>	145 mm	<b>Visor Plug front / rear</b>	Front
<b>Starter</b>	Electric and manual	<b>USB power outlet</b>	Yes, in front compartment
<b>Reverse</b>	RER	<b>LinQ attachment</b>	2 pairs

\* Vehicle overall length without snowflap.